


# Intrusion Detectors

## Internal Motion Detectors

### Wireless Detectors and Peripherals



Type			Order No.																										
IRCW6-11		<b>Multifunctional remote control</b> <p>The Intrunet wireless multifunctional remote control in stylish white color is smaller than a credit card and only a few millimeters thick. Besides common functions such as set, unset and part set, the remote control includes a programmable key for user-defined functions as well as an emergency function (panic alarm). Furthermore, batteries can easily be exchanged for maximum product life duration.</p> <table><tr><td>Power supply</td><td>Rechargeable battery</td></tr><tr><td>Current consumption</td><td>Standby: &lt;1 mA Max.: 28 mA</td></tr><tr><td>Battery</td><td>Lithium 3 V Type: CR2032</td></tr><tr><td>Frequency</td><td>868 MHz</td></tr><tr><td>Range</td><td>100 m at open space</td></tr><tr><td>Communication protocol</td><td>SiWay</td></tr><tr><td>Events</td><td>Set, unset, part set, optional: panic, control</td></tr><tr><td>Humidity (EN60721)</td><td>&lt;85% r.h., no condensation</td></tr><tr><td>Housing protection (EN 60529)</td><td>IP41 / IK02</td></tr><tr><td>Operating temperature</td><td>-10 ~ +50 °C</td></tr><tr><td>Dimensions (W x H x D)</td><td>30 x 57 x 13 mm</td></tr><tr><td>Weight</td><td>0.01 kg</td></tr><tr><td>Data sheet</td><td>009093</td></tr></table>	Power supply	Rechargeable battery	Current consumption	Standby: <1 mA Max.: 28 mA	Battery	Lithium 3 V Type: CR2032	Frequency	868 MHz	Range	100 m at open space	Communication protocol	SiWay	Events	Set, unset, part set, optional: panic, control	Humidity (EN60721)	<85% r.h., no condensation	Housing protection (EN 60529)	IP41 / IK02	Operating temperature	-10 ~ +50 °C	Dimensions (W x H x D)	30 x 57 x 13 mm	Weight	0.01 kg	Data sheet	009093	S54543-F109-A100
Power supply	Rechargeable battery																												
Current consumption	Standby: <1 mA Max.: 28 mA																												
Battery	Lithium 3 V Type: CR2032																												
Frequency	868 MHz																												
Range	100 m at open space																												
Communication protocol	SiWay																												
Events	Set, unset, part set, optional: panic, control																												
Humidity (EN60721)	<85% r.h., no condensation																												
Housing protection (EN 60529)	IP41 / IK02																												
Operating temperature	-10 ~ +50 °C																												
Dimensions (W x H x D)	30 x 57 x 13 mm																												
Weight	0.01 kg																												
Data sheet	009093																												