



Intrusion Detectors

Internal Motion Detectors

Wireless Detectors and Peripherals



Type		Order No.																				
ISRW6-12..	<p>Wireless outdoor siren (compatible with IC60 and SI series)</p> <p>The Intrunet outdoor siren communicates wirelessly thanks to an extension of the SiWay protocol named Si2Way. This communication protocol allows Si2Way components not only to send information to the control panel, but also to receive commands from the panel. The ISRW6-12.. comes with an embedded Si2Way radio module and powerful standard batteries ensuring a long maintenance cycles. The activation of the siren can be either time limited or disabled if required by the application. In addition to the powerful acoustic signal (100 dB at 1 m), an integrated light strobe flashes up siren activation.</p> <table><tr><td>Wireless protocol</td><td>Si2Way</td></tr><tr><td>Frequency</td><td>868 MHz</td></tr><tr><td>Wireless module range</td><td>Up to 300 m at open space</td></tr><tr><td>Sound level</td><td>Siren: 100 dB @ 1.00 m</td></tr><tr><td>Battery lifetime</td><td>3 years under normal conditions</td></tr><tr><td>Battery</td><td>ER34615M 3.6V, 14 Ah, D size</td></tr><tr><td>Housing protection (EN 60529)</td><td>IP54</td></tr><tr><td>Humidity (EN60721)</td><td><95% r.h., no condensation</td></tr><tr><td>Operating temperature</td><td>-20 ~ +70 °C</td></tr><tr><td>Storage temperature</td><td>-20 ~ +80 °C</td></tr></table>	Wireless protocol	Si2Way	Frequency	868 MHz	Wireless module range	Up to 300 m at open space	Sound level	Siren: 100 dB @ 1.00 m	Battery lifetime	3 years under normal conditions	Battery	ER34615M 3.6V, 14 Ah, D size	Housing protection (EN 60529)	IP54	Humidity (EN60721)	<95% r.h., no condensation	Operating temperature	-20 ~ +70 °C	Storage temperature	-20 ~ +80 °C	ISRW6-12..
Wireless protocol	Si2Way																					
Frequency	868 MHz																					
Wireless module range	Up to 300 m at open space																					
Sound level	Siren: 100 dB @ 1.00 m																					
Battery lifetime	3 years under normal conditions																					
Battery	ER34615M 3.6V, 14 Ah, D size																					
Housing protection (EN 60529)	IP54																					
Humidity (EN60721)	<95% r.h., no condensation																					
Operating temperature	-20 ~ +70 °C																					
Storage temperature	-20 ~ +80 °C																					
ISRW6-12R	<p>Wireless outdoor siren</p> <p>See ISRW6-12.. for technical overview and note the additional / other specifications:</p> <table><tr><td>Colour</td><td>Red</td></tr></table> 	Colour	Red	S54538-F103-A200																		
Colour	Red																					
ISRW6-12T	<p>Wireless outdoor siren in orange</p> <p>See ISRW6-12.. for technical overview and note the additional / other specifications:</p> <table><tr><td>Colour</td><td>Orange</td></tr></table> 	Colour	Orange	S54538-F103-A300																		
Colour	Orange																					